

Technical Product Data Sheet

Intertape® 54113



Intertape® 54113 is a PET Film Electrical Tape with a 1.0 mil polyester backing and a thermosetting acrylic adhesive. The tape exhibits high temperature shear resistance when thermoset. The backing provides abrasion and Puncture resistance and excellent insulating properties.

Nominal Values

PFT Film **Backing**

Backing Thickness 0,025 mm

> **Adhesive Type** Acrylic, thermosetting

Total Thickness 0,060 mm

Insulation Class B 130°C (DIN EN 60085, OANZ2 & OANZ8)

> Color Yellow (17), Clear (00)

Adhesion to Steel 12.30 N/25 mm

Tensile Strength 110,00 N/25 mm

Elongation at Break 100%

Dielectric Strength 5000 V

Insulation Resistance (megaΩ) $10^6\Omega$

> **Electrolytic Corrosion** A1,0

> > **Flammability** BU1

> > > Width

UL-File # E20780

Length 66 m, other lengths upon request

widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.


We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, other


Effective 05 December 2019







DE-79227 Schallstadt















Technical Product Data Sheet

Intertape® 54113



Applications

- Coil wrapping
- Tabbing and anchoring
- Inter-layer insulating
- Film wrap capacitors

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 18°C to 24°C, with a relative humidity of 40% to 50%. When using an adhesive tape stored below 18°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 03.11.2025





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the







