

Technical Product Data Sheet

Intertape® MM 149855

Intertape® MM (Mint Mask) 149855 is a mint green colored, saturated, crepe paper masking tape with pressure-sensitive rubber adhesive. It is conformable and has good adhesion and holding properties. Intertape® MM 149855 is smooth to unwind, resists paint flaking, performs well during wet sanding, and is clean and easy to remove. Compatible with both water and solvent based paints, it is UV-resistant for up to three days.

Nominal Values

Backing Crepe Paper

Adhesive Type Natural Rubber / Resins

Total Thickness 0,15 mm

Color Mint Green (81)

Adhesion to Steel 7,60 N/25 mm

Tensile Strength 96,20 N/25 mm

Elongation at Break 10%

Temperature Resistance +149°C (30 Min.)

Length 55 m, other lengths upon request

Width 1498 mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Additional Info Recommended hot to warm removal, but can be removed cold

Effective 27 May 2025





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of









DE-79227 Schallstadt



Technical Product Data Sheet

Intertape® MM 149855

Applications

Automotive, truck, bus, and marine paint masking

Benefits


- Conformable
- Good adhesion and holding properties
- · Clean, easy removal
- Smooth unwinding
- Resists paint flaking
- · Performs well during wet sanding
- Compatible with water and solvent based paints
- UV-resistant up to three days

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 06.08.2025















DE-79227 Schallstadt