IPG® (Intertape®) MM 149855

IPG® (Intertape®) MM (Mint Mask) 149855 is a mint green colored, saturated, crepe paper masking tape with pressure-sensitive rubber adhesive. It is conformable and has good adhesion and holding properties. IPG® (Intertape®) MM 149855 is smooth to unwind, resists paint flaking, performs well during wet sanding, and is clean and easy to remove. Compatible with both water and solvent based paints, it is UV-resistant for up to three days.

Nominal Values

Backing	Crepe Paper
Adhesive Type	Natural Rubber / Resins
Total Thickness	0,15 mm
Color	Mint Green (81)
Adhesion to Steel	7,60 N/25 mm
Tensile Strength	96,20 N/25 mm
Elongation at Break	10%
Temperature Resistance	+149°C (30 Min.)
Length	55 m, other lengths upon request
Width	1498 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Additional Info	Recommended hot to warm removal, but can be removed cold
Effective	27 May 2025

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

IPG® (Intertape®) MM 149855

Applications

- Automotive, truck, bus, and marine paint masking

Benefits

- Conformable
- Good adhesion and holding properties
- Clean, easy removal
- Smooth unwinding
- Resists paint flaking
- Performs well during wet sanding
- Compatible with water and solvent based paints
- UV-resistant up to three days

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 03.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com