

## IPG® (Intertape®) MM 149855

IPG® (Intertape®) MM (Mint Mask) 149855 is a mint green colored, saturated, crepe paper masking tape with pressure-sensitive rubber adhesive. It is conformable and has good adhesion and holding properties. IPG® (Intertape®) MM 149855 is smooth to unwind, resists paint flaking, performs well during wet sanding, and is clean and easy to remove. Compatible with both water and solvent based paints, it is UV-resistant for up to three days.

### Nominal Values

<b>Backing</b>	Crepe Paper
<b>Adhesive Type</b>	Natural Rubber / Resins
<b>Total Thickness</b>	0,15 mm
<b>Color</b>	Mint Green (81)
<b>Adhesion to Steel</b>	7,60 N/25 mm
<b>Tensile Strength</b>	96,20 N/25 mm
<b>Elongation at Break</b>	10%
<b>Temperature Resistance</b>	+149°C (30 Min.)
<b>Length</b>	55 m, other lengths upon request
<b>Width</b>	1498 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Additional Info</b>	Recommended hot to warm removal, but can be removed cold
<b>Effective</b>	27 May 2025

## IPG® (Intertape®) MM 149855

### Applications

- Automotive, truck, bus, and marine paint masking

### Benefits

- Conformable
- Good adhesion and holding properties
- Clean, easy removal
- Smooth unwinding
- Resists paint flaking
- Performs well during wet sanding
- Compatible with water and solvent based paints
- UV-resistant up to three days

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 30.06.2026