

Saint-Gobain / h-old® GL94



Saint-Gobain / h-old® GL94 is a glass cloth coated tape with a high quality acrylic adhesive system. Designed for coil wrapping, layer and crossover insulation, cable harnesses and all applications where mechanical and thermal resistance are required.

Nominal Values

| | |
|-------------------------------|---|
| Backing | Glass Cloth |
| Backing Thickness | 0,120 mm |
| Adhesive Type | Acrylic |
| Total Thickness | 0,165 mm |
| Insulation Class | F 155°C (DIN EN 60085, OANZ2 & OANZ8) |
| Color | White (08), Black (04), (Black (04) not UL-listed) |
| Adhesion to Steel | 10,00 N/25 mm, (90°) |
| Tensile Strength | 750,00 N/25 mm |
| Elongation at Break | 5% |
| Dielectric Strength | 2500 V |
| Electrolytic Corrosion | 1 |
| Rolling Ball Tack | < 10 cm |
| Temperature Resistance | +180°C, (short-term) |
| UL-File # | E178430 |
| Length | 50 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1200 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Effective | 29 March 2021 |

Saint-Gobain / h-old® GL94



Applications

- Motor and transformer manufacturers
- Capacitor and coil manufacturers
- Wiring harness Industry, automotive, home appliance

Benefits

- Good adhesion and ageing resistance
- Good chemical resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 12.02.2026