

Technical Product Data Sheet

Saint-Gobain / h-old® P34-00



Saint-Gobain / h-old® P34-00 is PET Film coated with high quality acrylic adhesive. It is designed for coil wrapping, inter-layer insulation, anchoring, holding, harnessing, splicing, etc.

Nominal Values

Backing PET Film

Backing Thickness 0,023 mm

> **Adhesive Type** Acrylic

Total Thickness 0,060 mm

Insulation Class B 130°C (DIN EN 60085, OANZ2 & OANZ8)

> Color Clear (00)

Adhesion to Steel 8,75 N/25 mm

Tensile Strength 100,00 N/25 mm

Elongation at Break 80%

Dielectric Strength 4500 V

Temperature Resistance +180°C, (short-term)

> UL-File # E178430

Length 66 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1280 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 29 March 2021







We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the









DE-79227 Schallstadt



Technical Product Data Sheet

Saint-Gobain / h-old® P34-00



Applications

- Coil wrapping
- Interlayer insulation coil wrapping, inter-layer insulation, anchoring, holding, harnessing, splicing, etc.
- Motor & transformer manufacturers
- Capacitor manufacturers
- Splicing of papers and films
- Identification

Benefits

- Good adhesion and initial tack
- High conformability and chemical resistance
- Excellent flagging and solvent resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 02.07.2025





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of









DE-79227 Schallstadt