

# **Technical Product Data Sheet**

## Saint-Gobain / h-old® X180



Saint-Gobain / h-old® X180 is Nomex® paper coated on one side with a rubber thermosetting adhesive system. Designed for high temperature electrical applications where a strong and puncture resistant backing is required. Availbale on white release paper liner on demanad.

#### **Nominal Values**

**Backing** Nomex®

**Backing Thickness** 0,180 mm

**Adhesive Type** Natural Rubber, thermosetting

**Total Thickness** 0,240 mm

**Insulation Class** F 155°C (DIN EN 60085, OANZ2 & OANZ8)

Color White (08)

Adhesion to Steel | 10,00 N/25 mm

**Tensile Strength** 500,00 N/25 mm

**Elongation at Break** 5%

**Dielectric Strength** 6700 V

**Electrolytic Corrosion** 1

**Rolling Ball Tack** < 10 cm

**Temperature Resistance** +180°C, (short-term)

**Length** 50 m, other lengths upon request

**Width** 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 914

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 29 March 2021















DE-79227 Schallstadt



# **Technical Product Data Sheet**

## Saint-Gobain / h-old® X180



### **Applications**

- Phase insulation of electrical motors, generators, etc.
- Outer wrapping, tabbing and anchoring leads of electrical transformers, coils, etc

#### **Benefits**

- Good thermal and puncture resistance
- High initial adhesion
- Good chemical resistance when thermoset

### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 31.10.2025





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the







