

tesa®ACXplus 7055

tesa® ACXplus 7055 is a highly transparent acrylic core tape designed for bonds that achieve a seamless and optical clear finish. Translucent and transparent materials, such as glass or acrylic are easy to bond with tesa® ACXplus 7055.

Nominal Values

Backing	solid Acrylic
Adhesive Type	Acrylic
Total Thickness	1,00 mm
Color	Clear (00)
Liner	Silicone-free film
Adhesion to Steel	60,00 N/25 mm (90°)
Tensile Strength	100 N/cm ²
Shear Strength	35 N/cm ²
Static Shear	3 cm ² / 72 h: 750 g (23°C), 500 g (70°C)
Temperature Resistance	+200°C (short-term), '+110°C (long-term)
Length	25 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 19 mm, 25 mm, 880 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Density	ca. 1030 kg/m ³
Effective	30 November 2024

tesa®ACXplus 7055

Applications

- Bonding transparent / translucent substrates
- Ideal for glass and acrylic substrates
- Extruded profiles
- Signage mounting
- Plisse profiles
- For Indoor and outdoor applications

Benefits

- Highly transparent
- Provides seamless and optical clear finish

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 19.08.2025