

## tesa®ACXplus 7055

tesa® ACXplus 7055 is a highly transparent acrylic core tape designed for bonds that achieve a seamless and optical clear finish. Translucent and transparent materials, such as glass or acrylic are easy to bond with tesa® ACXplus 7055.

### Nominal Values

<b>Backing</b>	solid Acrylic
<b>Adhesive Type</b>	Acrylic
<b>Total Thickness</b>	1,00 mm
<b>Color</b>	Clear (00)
<b>Liner</b>	Silicone-free film
<b>Adhesion to Steel</b>	60,00 N/25 mm (90°)
<b>Tensile Strength</b>	100 N/cm <sup>2</sup>
<b>Shear Strength</b>	35 N/cm <sup>2</sup>
<b>Static Shear</b>	3 cm <sup>2</sup> / 72 h: 750 g (23°C), 500 g (70°C)
<b>Temperature Resistance</b>	+200°C (short-term), '+110°C (long-term)
<b>Length</b>	25 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 19 mm, 25 mm, 880 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Density</b>	ca. 1030 kg/m <sup>3</sup>
<b>Effective</b>	30 November 2024

## tesa®ACXplus 7055

### Applications

- Bonding transparent / translucent substrates
- Ideal for glass and acrylic substrates
- Extruded profiles
- Signage mounting
- Plisse profiles
- For Indoor and outdoor applications

### Benefits

- Highly transparent
- Provides seamless and optical clear finish

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 10.12.2025