

volzAcrylicFoam 74200 PV1



volzAcrylicFoam 74200 PV1 is a 2,00 mm thick, double-sided, transparent, environmental-friendly (no VOC) acrylic foam tape. The clear acrylic adhesive is within the foam itself. It is stable in both high and low temperatures, remains strong under UV light, and is heat, chemical and moisture resistant. volzAcrylicFoam 74200 PV1 has an excellent holding power that withstands various weights in a multitude of environments.

Nominal Values

Backing	Acrylic Foam
Adhesive Type	Acrylic
Total Thickness	2,00 mm (± 10%)
Color	Clear (00)
Liner	red PE Film
Adhesion to Steel	36,75 N/25 mm
Shear Strength	9 kgf/cm ²
Static Shear	3,23 cm ² /168 h: 1000 g (23°C), 500 g (93°C)
Temperature Resistance	+150°C (short-term), +93°C (long-term)
Length	16,50 m, other lengths upon request
Width	4 mm – 450 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Slitting Tolerance	Length < 33m = ± 0,4mm (± 1/64"), Length > 33m = ± 0,8mm (± 1/32"), Lower tolerances on inquiry and perhaps against extra charge possible, Cross-wound spools are not similar to the above mentioned tolerances
Effective	24 April 2025

volzAcrylicFoam 74200 PV1



Applications

- Metal, glass, high surface energy plastics
- Decoration panels
- Joining clear materials
- Identification plates
- Signs

Benefits

- Excellent holding power
- No VOC - environmental friendly
- Stable in high and low temperatures
- Excellent UV Resistance
- Heat, chemical and moisture resistant

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 21°C to 30°C, with a relative humidity of 50%. When using an adhesive tape stored below 21°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 14.05.2026