

volzAcrylicFoam 75060 PV1

volzAcrylicFoam 75060 PV1 is an acrylic foam tape with a modified acrylic adhesive designed for use on low-surface-energy surfaces. Thanks to its excellent adhesive strength, it is suitable for use in the automotive, electronics, and construction industries. volzAcrylicFoam 75060 PV1 has high initial tack and can be used on low-surface-energy materials such as PP, PS, and powder-coated plastics.

Nominal Values

Backing	Acrylic Foam
Adhesive Type	LSE Acrylic
Total Thickness	0,60 mm (± 10%)
Color	Black (04)
Liner	PE Film
Adhesion to Steel	39,23 N/25 mm
Shear Strength	9 kgf/cm ²
Static Shear	3,23 cm ² /168 h: 1500 g (23°C), 750 g (93°C)
Temperature Resistance	+90°C, +70°C (long-term)
Length	33 m, other lengths upon request
Width	19 mm, 25 mm, 38 mm, 50 mm, 930 mm, Other widths by request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	13 October 2026

volzAcrylicFoam 75060 PV1

Applications

- Bonding of materials with low surface energy, such as PP, PS, and powder-coated plastics
- Applications in the automotive industry, the electronics sector, and the construction industry.

Benefits

- Very good adhesion
- Excellent initial tack

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 21°C to 38°C, with a relative humidity of 50%. When using an adhesive tape stored below 21°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 17.10.2026