

volzAcrylicFoam 76025 PV1

volzAcrylicFoam 76025 PV1 is a double-sided adhesive tape consisting of an acrylic adhesive coated on an acrylic foam carrier. With excellent adhesion power, it is most often used in the automotive, electronics and construction industries. volzAcrylicFoam 76025 PV1 has excellent holding power and temperature resistance, and can withstand extreme weights and heat.

Nominal Values

Backing	Acrylic Foam
Adhesive Type	Acrylic
Total Thickness	0,250 mm (±10%)
Color	Black (04)
Liner	red, siliconized, PE Film
Adhesion to Steel	31,87 N/25 mm
Shear Strength	8 kgf/cm ²
Static Shear	3,23 cm ² /168 h: 1000 g (23°C), 500 g (93°C)
Temperature Resistance	+150°C (short-term), +93°C (long-term)
Length	33 m, other lengths upon request
Width	4 mm – 930 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	12 February 2026

volzAcrylicFoam 76025 PV1

Applications

- Metal, glass, high surface energy plastics
- Automotive
- Construction

Benefits

- Excellent adhesion and holding power
- Superb temperature resistance
- Withstands extreme weights and heat

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 21°C to 30°C, with a relative humidity of 50%. When using an adhesive tape stored below 21°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 27.04.2026