

volzBand 31800 PV1

volzBand 31800 PV1 is a premium, heavy-duty, LDPE extruded cloth tape with a natural rubber adhesive. It combines extra thickness with exceptional adhesion and tensile strength, ensuring performance under extreme stress.

Nominal Values

| | |
|--------------------------|--|
| Backing | LDPE extruded Cloth |
| Adhesive Type | Natural Rubber |
| Total Thickness | 0,400 mm |
| Color | Black (04), Grey (55) |
| Adhesion to Steel | 24,50 N/25 mm |
| Tensile Strength | 196,00 N/25 mm |
| Length | 50 m, 500 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1250 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 6 months. |
| Effective | 24 April 2025 |

volzBand 31800 PV1

Applications

- Typical repair tape that can be used in a variety of applications
- Marking, covering, packaging, protecting, sealing
- Securing cables
- Floor markings
- Fastening structures
- General marking work
- Sealing bags and cardboard boxes

Benefits

- Premium quality
- Exceptional adhesion and tensile strength
- Performs under extreme stress

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 07.12.2025