

## volzBand 31800 PV1

volzBand 31800 PV1 is a premium, heavy-duty, LDPE extruded cloth tape with a natural rubber adhesive. It combines extra thickness with exceptional adhesion and tensile strength, ensuring performance under extreme stress.

### Nominal Values

<b>Backing</b>	LDPE extruded Cloth
<b>Adhesive Type</b>	Natural Rubber
<b>Total Thickness</b>	0,400 mm
<b>Color</b>	Black (04), Grey (55)
<b>Adhesion to Steel</b>	24,50 N/25 mm
<b>Tensile Strength</b>	196,00 N/25 mm
<b>Length</b>	50 m, 500 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1250 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 6 months.
<b>Effective</b>	24 April 2025

## volzBand 31800 PV1

### Applications

- Typical repair tape that can be used in a variety of applications
- Marking, covering, packaging, protecting, sealing
- Securing cables
- Floor markings
- Fastening structures
- General marking work
- Sealing bags and cardboard boxes

### Benefits

- Premium quality
- Exceptional adhesion and tensile strength
- Performs under extreme stress

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 24.06.2026