

# volzBand 6014

volzCloth 6014 is a general purpose tape suitable for bundling, sealing, seaming, repairing, holding, plumbing and waterproofing. The tape is built with an polyethylene backing which is reinforced with polyester cloth and coated with an Hotmelt adhesive

## Nominal Values

<b>Backing</b>	PE film reinforced with polyester cloth
<b>Backing Thickness</b>	0,055 mm
<b>Adhesive Type</b>	Clear Hotmelt Synthetic Rubber
<b>Total Thickness</b>	0,180 mm
<b>Color</b>	Silver (34)
<b>Adhesion to Steel</b>	18,75 N/25 mm
<b>Tensile Strength</b>	75,00 N/25 mm
<b>Elongation at Break</b>	15%
<b>Length</b>	50 m, other lengths upon request
<b>Width</b>	48 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	26 March 2025

## volzBand 6014

### Applications

- Suitable for bundling, sealing, seaming, repairing, holding, plumbing and waterproofing

### Benefits

- Excellent adhesion and conformability
- Excellent tack
- Long lasting adhesion
- Waterproof backing
- Hand tearable

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.05.2026