

volzBand 6014

volzCloth 6014 is a general purpose tape suitable for bundling, sealing, seaming, repairing, holding, plumbing and waterproofing. The tape is built with an polyethylene backing which is reinforced with polyester cloth and coated with an Hotmelt adhesive

Nominal Values

Backing	PE film reinforced with polyester cloth
Backing Thickness	0,055 mm
Adhesive Type	Clear Hotmelt Synthetic Rubber
Total Thickness	0,180 mm
Color	Silver (34)
Adhesion to Steel	18,75 N/25 mm
Tensile Strength	75,00 N/25 mm
Elongation at Break	15%
Length	50 m, other lengths upon request
Width	48 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	26 March 2025

volzBand 6014

Applications

- Suitable for bundling, sealing, seaming, repairing, holding, plumbing and waterproofing

Benefits

- Excellent adhesion and conformability
- Excellent tack
- Long lasting adhesion
- Waterproof backing
- Hand tearable

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 23.07.2025