

## volzBand 6057V



volzBand 6057V is manufactured from a rayon cloth carrier with high performance rubber adhesive on the surface and a special resin on the backside. The surface does not contain a silicone release.

### Nominal Values

<b>Backing</b>	Rayon Cloth, Acrylic Coated
<b>Backing Thickness</b>	0,190 mm
<b>Adhesive Type</b>	Natural Rubber, thermosetting
<b>Total Thickness</b>	0,230 mm
<b>Color</b>	Grey (55)
<b>Adhesion to Steel</b>	9,90 N/25 mm
<b>Tensile Strength</b>	146,00 N/25 mm
<b>Elongation at Break</b>	10%
<b>Dielectric Strength</b>	1500 V
<b>Temperature Resistance</b>	+160°C, +180°, +260°C, (short-term), +160°C für 2 h, +180°C für 0,5 h, +260°C für 10 Sec.
<b>Length</b>	50 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 975 mm, 1020 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	03 December 2020

## volzBand 6057V



### Applications

- Covering gold contacts during dip soldering
- Masking of transformer parts during impregnation
- Final coil bandaging
- Cable bandaging of motor area
- Masking during sandblasting
- Masking of window frames
- Masking of holes and joints
- Window fixation during drying process

### Benefits

- Insensitive to oils and plasticizer resistant
- Resistant to impregnating agents

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 31.05.2026