

Technical Product Data Sheet

volzDispenser 161-0624



volzDispenser 161-0624-60/120/180 dispenses all common and special adhesive labels quickly and easily. Scanning is photo-electric. The dispensing speed and the label feed are infinitely variable. The built-in counter displays how many labels have been dispensed.

Nominal Values

Length Calibration Control Panel, continuously variable

Nominal Voltage 100 – 240 VAC, 50/60 Hz

Power Consumption 161-0624-120: 45 W, 161-0624-180: 50 W, 161-0624-60: 40 W

Tape Width 161-0624-120: 15 mm – 120 mm, 161-0624-180: 15 mm – 180 mm,

161-0624-60: 200 mm

Tape Length 10 mm – 999 mm

Max. Roll Diameter 161-0624-120: 250 mm, 161-0624-180: 300mm, 161-0624-60: 200 mm

Type of Rolls Die-Cut Rolls, Label Rolls

Required Space (LxWxH) 161-0624-120: 231 mm x 164 mm x 157mm, 161-0624-180: 241 mm x 224

mm x 157 mm, 161-0624-60; 215 mm x 104 mm x 140 mm

Weight 161-0624-120: 3030 kg, 161-0624-180: 4,60 kg, 161-0624-60: 2,10 kg

Type Automatic

Effective 18 March 2024















DE-79227 Schallstadt



Technical Product Data Sheet

volzDispenser 161-0624



Applications

- Label Dispenser
- Die-Cut Tape Dispenser

Benefits

- Available in three different sizes
- Dispenses very quickly and easily
- Dispenses very quickly and easily
- Built-in digital counter
- Two counting functions: total number of pieces, and count-down of the programmed number of pieces Compact design

Print Date: 15.05.2024





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of







