

volzElektro 1401AC



volzElektro 1401AC is a Teonex® film coated on one side with high-temperature acrylic adhesive. Designed for high temperature electrical applications where a thin, strong backing combined with excellent dielectrical properties are required.

Nominal Values

Manufacturer	VOLZ®
Backing	Teonex® Film
Backing Thickness	0,050 mm
Adhesive Type	Acrylic
Total Thickness	0,085 mm
Insulation Class	F 155°C (DIN EN 60085, OANZ2 & OANZ8)
Color	Blue (11)
Adhesion to Steel	11,25 N/25 mm
Tensile Strength	225,00 N/25 mm
Elongation at Break	60%
Breakdown Voltage	8000 V
Electrolytic Corrosion	1
Rolling Ball Tack	< 10 cm
Temperature Resistance	+220°C, (short term)
Length	66 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 75 mm, 1000 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	20 October 2020

volzElektro 1401AC



Applications

- Insulation of bobbins, pencil coils, transformers, motors, capacitors, etc.
- Cable and copper wire manufacturers

Benefits

- High Temperature Resistance
- Good Adhesion on Difficult Substrates
- Good Chemical and Solvent Resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2024