

volzElektro 4384 PV1



volzElektro 4384 PV1 consists of high tear-resistant copper film, laminated with a acrylic adhesive filled with silver particles. It provides a high conductivity. The adhesive tape has a silicone paper liner. volzElektro 4384 PV1 is solderable and is very good for a variety of applications in EMI / ESD.

Nominal Values

Manufacturer	VOLZ®
Backing	Copper Film
Backing Thickness	0,025 mm
Adhesive Type	Acrylic, with silver particles
Total Thickness	0,065 mm
Adhesion to Steel	7,12 N/25 mm
Tensile Strength	6,87 N/25 mm
Temperature Resistance	+180°C
Length	33 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	04 December 2019

volzElektro 4384 PV1



Applications

- PCB production
- EMV shielding
- Shielding of cables and connector grounding of electrical devices
- Drain off electrostatic charges

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.07.2024