

volzElektro 4384 PV2

volzElektro 4384 PV2 consists of high tear-resistant copper film, with a conductive, pressure-sensitive acrylic adhesive. It is both single and double conductive, provides EMI shielding, and is flame retardant. volzElektro 4384 PV2 also is UV, moisture, chemical and corrosion resistant. It is extremely durable and ideal for outdoor applications.

Nominal Values

Backing	Copper Film
Backing Thickness	0,035 mm
Adhesive Type	Conductive Acrylic
Total Thickness	0,075 mm
Liner	Siliconized Paper
Adhesion to Steel	> 10 N/25 mm
Shear Strength	> 24
Temperature Resistance	-20°C to +120°C
Length	33 m, other lengths upon request
Width	19 mm, 25 mm, 38 mm, 50 mm, 380 mm, Other widths by request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	16 April 2026

volzElektro 4384 PV2

Applications

- Single and double conductive
- Ideal for use in transformer, mobile phone, computer, PDA, PDP, LCD monitor, PC, and copier manufacturing
- Commonly used in the fridge, air-conditioning, automotive, bridge, hotel and electronic industries
- Excellent for outdoor applications

Benefits

- Strong adhesion
- Waterproof
- Resistant to both cold and hot temperatures
- Flame retardant
- Moisture, UV, chemical and corrosion resistant
- Provides EMI shielding
- Strong heat preservation and and insulation
- Excellent appearance with no oxidation

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 21.06.2026