

volzElektro 5060 PV3

volzElektro 5060 PV3 is manufactured from strong, acetate cloth with a thermosetting, acrylic-based, pressure-sensitive adhesive. With highly conformable and Strong adhesion, it is suitable for wrapping coil, Holding transformers or Repairing electrical equipment. The tape is oil resistant.

Nominal Values

Manufacturer	VOLZ®
Backing	Silk Acetate Cloth
Backing Thickness	0,180 mm
Adhesive Type	Acrylic, thermosetting
Total Thickness	0,240 mm
Insulation Class	B 130°C (DIN EN 60085, OANZ2 & OANZ8)
Color	Black (04)
Adhesion to Steel	11,80 N/25 mm
Tensile Strength	157,00 N/25 mm
Elongation at Break	16%
Breakdown Voltage	2500 V
Temperature Resistance	-30°C to +130°C
UL-File #	E338128
Length	30 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1040 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	01 September 2023

volzElektro 5060 PV3

Applications

- Coil wrapping
- Tapping
- Inter-layer insulation
- Repairing electrical equipment
- Holding transformers

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.07.2024