volzElektro 6017 PV5



volzElektro 6017 PV5 is a glass cloth electrical tape manufactured from an electrical grade fiberglass cloth with high performance thermosetting acrylic adhesive. The tape has excellent resistance to solvents. For coil coverings, layer and wire harness applications.

Nominal Values

Backing	Glass Cloth, printable, oil resistant
Backing Thickness	0,135 mm
Adhesive Type	Acrylic, thermosetting
Total Thickness	0,190 mm
Insulation Class	F 155°C (DIN EN 60085, OANZ2 & OANZ8)
Color	White (08), Black (04)
Adhesion to Steel	12,70 N/25 mm
Tensile Strength	784 N/25 mm
Elongation at Break	14%
Dielectric Strength	4000 V
Temperature Resistance	-29°C up AE47+177°C
UL-File #	E338128
Length	55 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1245 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	08 March 2022

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzElektro 6017 PV5



Applications

- Inter-layer insulation
- Coil outer wraps
- Tie-downs
- Lead insulation and protection
- Electrical motor and generator binding

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com