

## volzElektro 6018 PV4



volzElektro 6018 PV4 consists of a highly tear-resistant glass fabric backing coated with a thermosetting silicone adhesive. The tape is flame retardant and therefore UL 510 listed. It is suitable for use at high continuous temperatures of up to 200°C..

### Nominal Values

<b>Backing</b>	Glass Cloth
<b>Backing Thickness</b>	0,120 mm
<b>Adhesive Type</b>	Silicone, thermosetting
<b>Total Thickness</b>	0,180 mm
<b>Insulation Class</b>	N 200°C (DIN EN 60085 & OANZ2), C (OANZ8)
<b>Color</b>	White (08)
<b>Adhesion to Steel</b>	9,80 N/25 mm
<b>Tensile Strength</b>	558,00 N/25 mm
<b>Elongation at Break</b>	10%
<b>Dielectric Strength</b>	3500 V
<b>UL-File #</b>	E338128
<b>Length</b>	33 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1075 mm, other widths upon request
<b>Storage Life Effective</b>	The material can be stored at room temperature for at least 12 months. 15 February 2021

## volzElektro 6018 PV4



### Applications

- High temperature coil insulation wrap
- Harness wrapping
- Splicing
- Motor repair shops
- Bundling and banding heavy gauge magnet wire
- Slot cell edge taping

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 10.04.2025