

Technical Product Data Sheet

volzElektro CP50



volzElektro CP50 is a 110 micron cellulose paper coated on one side with a rubber thermosetting adhesive system. Designed for holding and bundling applications where a conformable and hand tearable material is required.

Nominal Values

Backing Crepe Paper

Backing Thickness 0,110 mm

> **Adhesive Type** Natural Rubber, thermosetting

Total Thickness 0,150 mm

> Color Beige (24)

Adhesion to Steel 6,25 N/25 mm

Tensile Strength 112,50 N/25 mm

Elongation at Break 9%

Dielectric Strength 1000 V

Electrolytic Corrosion

Rolling Ball Tack < 10 cm

Temperature Resistance +130°C, (short-term)

> Length 50 m, other lengths and spools upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 09 December 2021





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of











Technical Product Data Sheet

volzElektro CP50



Applications

- Used for coil cover on boobbin wound coils
- Outer wrapping, tabbing and anchoring leads of small transformers, coils, etc.

Benefits

• Good conformability and puncture resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 03.11.2025







We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the









DE-79227 Schallstadt