

volzFilament 5079 PV2

volzFilament 5079 PV2 consists of a cross-woven, fiberglass-filament reinforced BOPP with a clear, synthetic rubber and hydrocarbon resin adhesive. It is suitable for reinforcing, bundling, palletising and packaging.

Nominal Values

Backing	Cross-Woven, Fiberglass-Filament, Reinforced BOPP
Backing Thickness	0,025 mm
Adhesive Type	Clear Hotmelt Synthetic Rubber
Total Thickness	0,120 mm
Color	Clear (00)
Adhesion to Steel	25,00 N/25 mm
Tensile Strength	600,00 N/25 mm
Elongation at Break	5%
Length	50 m, other lengths upon request
Width	19 mm, 25 mm, 50 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	24 March 2025

volzFilament 5079 PV2

Applications

- Reinforcing, bundling and packaging of heavy packed goods, profiles & tubes
- Pallet security

Benefits

- Excellent adhesion and tack High tensile strength

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 13.12.2025