

## volzFilament 5079 PV2

volzFilament 5079 PV2 consists of a cross-woven, fiberglass-filament reinforced BOPP with a clear, synthetic rubber and hydrocarbon resin adhesive. It is suitable for reinforcing, bundling, palletising and packaging.

### Nominal Values

<b>Backing</b>	Cross-Woven, Fiberglass-Filament, Reinforced BOPP
<b>Backing Thickness</b>	0,025 mm
<b>Adhesive Type</b>	Clear Hotmelt Synthetic Rubber
<b>Total Thickness</b>	0,120 mm
<b>Color</b>	Clear (00)
<b>Adhesion to Steel</b>	25,00 N/25 mm
<b>Tensile Strength</b>	600,00 N/25 mm
<b>Elongation at Break</b>	5%
<b>Length</b>	50 m, other lengths upon request
<b>Width</b>	19 mm, 25 mm, 50 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	24 March 2025

## volzFilament 5079 PV2

### Applications

- Reinforcing, bundling and packaging of heavy packed goods, profiles & tubes
- Pallet security

### Benefits

- Excellent adhesion and tack High tensile strength

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 26.07.2025