

volzFix 11965 PV1



volzFix 11965 PV1 is a double-sided adhesive tape consisting of a polyester film with excellent adhesion and very good tack. It has a reliable adhesive effect even under high external force and temperature. It is also very temperature-resistant.

Nominal Values

| | |
|-------------------------------|---|
| Backing | PET Film |
| Backing Thickness | 0,025 mm |
| Adhesive Type | Solvent Acrylic |
| Total Thickness | 0,205 mm |
| Color | Black (04) |
| Liner | 90 g, yellow, siliconized Paper |
| Adhesion to Steel | 17,00 N/25 mm |
| Shear Strength | ≥ 17 h |
| Temperature Resistance | -40°C to +180°C |
| Length | 50 m, 100 m, 700 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1240 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Effective | 05 December 2022 |

volzFix 11965 PV1



Applications

- Suitable for mounting and fastening of nameplates and membrane switches
- Good for bonding rigid-to-rigid substrates
- For dimensional stability and improved handling with easy die-cutting and laminating
- Adhesion to plastic and foam, attaches gaskets and LED lenses on cellular phones and pagers

Benefits

- Excellent adhesion
- Very good tack
- High temperature resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 01.08.2025