

## volzFix 9017 PV3

volzFix 9017 PV3 is a double sided adhesive tape where each side has a different adhesive strength. The low-adhesion side ensures residue-free removability, while the high-adhesion side guarantees optimum adhesion on smooth surfaces.

### Nominal Values

<b>Backing</b>	PET Film
<b>Backing Thickness</b>	0,023 mm
<b>Adhesive Type</b>	Covered side: Acrylic-based removable adhesive, Open side: Modified acrylic-based adhesive
<b>Total Thickness</b>	0,100 mm (without Liner)
<b>Color</b>	Clear (00)
<b>Adhesion to Steel</b>	3,00 N/25 mm (abgedeckte Seite / covered side), 20,00 N/25 mm (offene Seite/open Side)
<b>Temperature Resistance</b>	-40°C bis +70°C, +120°C (short-term)
<b>Length</b>	50 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	07 October 2025

# volzFix 9017 PV3

## Applications

- Masking of parts during powder coating
- Mounting of protection pads
- Mounting of shop front and window graphics
- Mounting of smart cards
- Protection of bright parts
- Application tape for auto badges
- Temporary fixing in print finishing and direct mail companies

## Benefits

- Easy to remove without leaving residue
- Permanent & non-permanent adhesive sides
- Good UV resistance

## Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 10.01.2026