

# **Technical Product Data Sheet**

## volzFix 9017 PV3

volzFix 9017 PV3 is a double sided adhesive tape where each side has a different adhesive strength. The low-adhesion side ensures residue-free removability, while the high-adhesion side guarantees optimum adhesion on smooth surfaces.

### **Nominal Values**

PET Film **Backing** 

**Backing Thickness** 0.023 mm

> Covered side: Acrylic-based removable adhesive, Open side: Modified **Adhesive Type**

> > acrylic-based adhesive

**Total Thickness** 0,100 mm (without Liner)

> Color Clear (00)

**Adhesion to Steel** 3,00 N/25 mm (abgedeckte Seite / covered side), 20,00 N/25 mm (offene

Seite/open Side)

**Temperature Resistance** -40°C bis +70°C, +120°C (short-term)

> Length 50 m, other lengths upon request

Width 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 07 October 2025





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of











# **Technical Product Data Sheet**

## volzFix 9017 PV3

### **Applications**

- · Masking of parts during powder coating
- Mounting of protection pads
- Mounting of shop front and window graphics
- Mounting of smart cards
- Protection of bright parts
- · Application tape for auto badges
- Temporary fixing in print finishing and direct mail companies

#### **Benefits**

- Easy to remove without leaving residue
- Permanent & non-permanent adhesive sides
- Good UV resistance

#### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 31.10.2025







We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the







