

Technical Product Data Sheet

volzFix 9017F



volzFix 9017F is a double-sided, adhesive tape with a PET-carrier and a modified-acrylic dispersion adhesive that has a different adhesive strength on each side. The open side is permanent sticking, the closed side is removable.

Nominal Values

Manufacturer **VOLZ®**

> **Backing** PETP Film

modified, Dispersion Acrylic, different adhesion on each side, open side(O): **Adhesive Type**

permanent sticking, closed side(G): removable

Total Thickness 0,160 mm

> Color Clear (00)

Liner siliconized Paper

Adhesion to Steel O: >15,00 N/25 mm, G: >5,00 N/25 mm

Temperature Resistance -30°C to +120°C

> Length 5 m, 25 m, 50 m, 500 m, 1200 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1050 Width


mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 09 March 2021







DE-79227 Schallstadt

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of











Technical Product Data Sheet

volzFix 9017F



Applications

- Bonding with resumption function
- Process aids for industry
- Event technology
- Exhibition tape
- Object renovations

Benefits

- Open side is permanent sticking
- Closed side is removable
- High condensation resistance
- High aging resistance
- Limited plasticizer resistance on the open side
- Very high plasticizer resistance on the closed side

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.07.2024













DE-79227 Schallstadt