

volzFix 9017F



volzFix 9017F is a double-sided, adhesive tape with a PET-carrier and a modified-acrylic dispersion adhesive that has a different adhesive strength on each side. The open side is permanent sticking, the closed side is removable.

Nominal Values

Manufacturer	VOLZ®
Backing	PETP Film
Adhesive Type	modified, Dispersion Acrylic, different adhesion on each side, open side(O): permanent sticking, closed side(G): removable
Total Thickness	0,160 mm
Color	Clear (00)
Liner	siliconized Paper
Adhesion to Steel	O: >15,00 N/25 mm, G: >5,00 N/25 mm
Temperature Resistance	-30°C to +120°C
Length	5 m, 25 m, 50 m, 500 m, 1200 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1050 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	09 March 2021

volzFix 9017F



Applications

- Bonding with resumption function
- Process aids for industry
- Event technology
- Exhibition tape
- Object renovations

Benefits

- Open side is permanent sticking
- Closed side is removable
- High condensation resistance
- High aging resistance
- Limited plasticizer resistance on the open side
- Very high plasticizer resistance on the closed side

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 21.11.2024