

volzFix 9017F



volzFix 9017F is a double-sided, adhesive tape with a PET-carrier and a modified-acrylic dispersion adhesive that has a different adhesive strength on each side. The open side is permanent sticking, the closed side is removable.

Nominal Values

Backing	PETP Film
Adhesive Type	modified, Dispersion Acrylic, different adhesion on each side, open side(O): permanent sticking, closed side(G): removable
Total Thickness	0,160 mm
Color	Clear (00)
Liner	siliconized Paper
Adhesion to Steel (N/25mm)	G: >5,00 N/25 mm, O: >15,00 N/25 mm
Temperature Resistance	-30°C to +120°C
Length	5 m, 25 m, 50 m, 500 m, 1200 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1050 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	09 March 2021

volzFix 9017F



Applications

- Bonding with resumption function
- Process aids for industry
- Event technology
- Exhibition tape
- Object renovations

Benefits

- Open side is permanent sticking
- Closed side is removable
- High condensation resistance
- High aging resistance
- Limited plasticizer resistance on the open side
- Very high plasticizer resistance on the closed side

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 27.04.2024