

Technical Product Data Sheet

volzFix 9028



volzFix 9028 is a double-sided adhesive tape consisting of a clear, polyester-film carrier and a modified solvent acrylic. The tape has a high initial tack.

Nominal Values

PET Film **Backing**

Backing Thickness 0,012 mm

> **Adhesive Type** modified, Solvent Acrylic

Total Thickness 0,125 mm

> Color Clear (00)

Liner 90 g, white, PE Paper

Adhesion to Steel ≥ 17,50 N/25 mm

Shear Strength ≥ 168 h

Rolling Ball Tack ≥ 3 cm

Temperature Resistance -40°C to +100°C, -40°C to +180°C (short-term)

> Length 5 m, 25 m, 50 m, 500 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1240 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 09 March 2021





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the











Technical Product Data Sheet

volzFix 9028



Applications

- Particularly suitable for bonding to both smooth and rough surfaces
- Bonding of signs, scales and aperture of plastic and metal
- Splicing of components in the electronics industry
- Bonding stripes and profiles made of wood or plastic
- Widely used in membrane switch and electrical industry (e.g. smart phones) as well as LCD technology
- All applications where thinness and high transparency are required

Benefits

- Good balance between adhesion and static shear, also in higher temperatures
- Thin and transparent with good adhesion
- Good resistant to moisture which works well in a wet environment
- Allows secure bonding to high energy surface substrates
- High energy plastics: PVC, ABS

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 02.11.2025



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.









