

## volzFix 9064



volzFix 9064 consists of a tear-resistant, flexible-cloth carrier coated on both sides with a significant amount of adhesive. It is Universally applicable and, due to its structure, especially suitable for bonding on rough adhesive surfaces. The product can be removed from all clean and crevice resistant surfaces without residue. Preliminary testing is suggested for bonding of plasticized materials.

### Nominal Values

<b>Manufacturer</b>	VOLZ®
<b>Backing</b>	Cotton Cloth
<b>Adhesive Type</b>	Natural Rubber
<b>Total Thickness</b>	0,340 mm
<b>Color</b>	White (08)
<b>Liner</b>	siliconized Paper
<b>Adhesion to Steel</b>	9,00 N/25 mm
<b>Tensile Strength</b>	140,00 N/25 mm
<b>Shear Strength</b>	> 24 h
<b>Temperature Resistance</b>	-20°C to +80°C
<b>Length</b>	50 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1040 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	24 September 2020

## volzFix 9064



### Applications

- Universally applicable
- Especially good for bonding on rough adhesive surfaces
- Splicing of fabric webs
- Securing panels for printing
- Laying of plastic flooring and carpet with structured backings
- Self-adhesive finishing of decorative material
- Lamination of shoe inserts and heel pads

### Benefits

- Can be removed from all clean and gap-solid surfaces without leaving residue
- Tear resistant, flexible cloth backing
- Limited aging and temperature resistance

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.07.2024