

volzFix 9064



volzFix 9064 consists of a tear-resistant, flexible-cloth carrier coated on both sides with a significant amount of adhesive. It is Universally applicable and, due to its structure, especially suitable for bonding on rough adhesive surfaces. The product can be removed from all clean and crevice resistant surfaces without residue. Preliminary testing is suggested for bonding of plasticized materials.

Nominal Values

Backing	Cotton Cloth
Adhesive Type	Natural Rubber
Total Thickness	0,340 mm
Color	White (08)
Liner	siliconized Paper
Adhesion to Steel	9,00 N/25 mm
Tensile Strength	140,00 N/25 mm
Shear Strength	> 24 h
Temperature Resistance	-20°C to +80°C
Length	50 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1040 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	24 September 2020

volzFix 9064



Applications

- Universally applicable
- Especially good for bonding on rough adhesive surfaces
- Splicing of fabric webs
- Securing panels for printing
- Laying of plastic flooring and carpet with structured backings
- Self-adhesive finishing of decorative material
- Lamination of shoe inserts and heel pads

Benefits

- Can be removed from all clean and gap-solid surfaces without leaving residue
- Tear resistant, flexible cloth backing
- Limited aging and temperature resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 12.02.2026