

volzFix 9064F



volzFix 9064is a double-sided self-adhesive tape with a cotton fabric backing , white differentiated strong/weak natural rubber adhesive. The closed side is permanently adhesive and the open-side is removable. This plasticiser resistant, trade show installation tape is removable from all surfaces without leaving residues even after a period of weeks.

Nominal Values

Backing	Cotton Cloth
Adhesive Type	Natural Rubber, different adhesion on each side, different adhesion on each side, open side: removable, closed side: permanent sticking
Total Thickness	0,340 mm
Insulation Class	A 105°C (DIN EN 60085)
Color	White (08)
Liner	65 g, White, siliconized Film
Length	5 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 36 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	06 December 2021



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Phone: +49 (0)7664 50500-0 info@volztapes.com Fax: +49 (0)7664 50500-50 www.volztapes.com









UL-Zertifizierter Konfektionär UL-zertifizierter Konfektionär



volzFix 9064F



Applications

• Perfect Exhibition tape

Benefits

- Can be removed from all surfaces without leaving residue, even after weeks
- Plasticiser resistant Limited aging and temperature resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 08.08.2025



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Phone: +49 (0)7664 50500-0 info@volztapes.com Fax: +49 (0)7664 50500-50 www.volztapes.com









