

volzFix 9064V



volzFix 9064V is a tear-resistant tape coated on both sides, consisting of a cloth carrier and a rubber adhesive. It can be used universally and is suitable for bonding rough surfaces and can be removed without residue.

Nominal Values

| | |
|-------------------------------|---|
| Backing | Cotton Cloth |
| Adhesive Type | Natural Rubber |
| Total Thickness | 0,300 mm |
| Color | White (08) |
| Liner | 78 g, brown, bi-siliconized, Paper |
| Adhesion to Steel | O: 2,50 N/25 mm, G: 6,50 N/25 mm |
| Tensile Strength | 159,00 N/25 mm |
| Temperature Resistance | +80°C |
| Length | 50 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Effective | 23 December 2022 |

volzFix 9064V



Applications

- Universally applicable
- Especially good for bonding on rough adhesive surfaces
- Splicing of fabric webs
- Securing panels for printing
- Laying of plastic flooring and carpet with structured backings
- Self-adhesive finishing of decorative material
- Lamination of shoe inserts and heel pads

Benefits

- Can be removed from all clean and gap-solid surfaces without leaving residue
- Tear resistant, flexible cloth backing
- Limited aging and temperature resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 03.07.2026