

## volzFix 9064V



volzFix 9064V is a tear-resistant tape coated on both sides, consisting of a cloth carrier and a rubber adhesive. It can be used universally and is suitable for bonding rough surfaces and can be removed without residue.

### Nominal Values

<b>Manufacturer</b>	VOLZ®
<b>Backing</b>	Cotton Cloth
<b>Adhesive Type</b>	Natural Rubber
<b>Total Thickness</b>	0,300 mm
<b>Color</b>	White (08)
<b>Liner</b>	78 g, brown, bi-siliconized, Paper
<b>Adhesion to Steel</b>	O: 2,50 N/25 mm, G: 6,50 N/25 mm
<b>Tensile Strength</b>	159,00 N/25 mm
<b>Temperature Resistance</b>	+80°C
<b>Length</b>	50 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	23 December 2022

## volzFix 9064V



### Applications

- Universally applicable
- Especially good for bonding on rough adhesive surfaces
- Splicing of fabric webs
- Securing panels for printing
- Laying of plastic flooring and carpet with structured backings
- Self-adhesive finishing of decorative material
- Lamination of shoe inserts and heel pads

### Benefits

- Can be removed from all clean and gap-solid surfaces without leaving residue
- Tear resistant, flexible cloth backing
- Limited aging and temperature resistance

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 21.11.2024