

Technical Product Data Sheet

volzFix 9064V



volzFix 9064V is a tear-resistant tape coated on both sides, consisting of a cloth carrier and a rubber adhesive. It can be used universally and is suitable for bonding rough surfaces and can be removed without residue.

Nominal Values

Cotton Cloth **Backing**

Adhesive Type Natural Rubber

Total Thickness 0,300 mm

> Color White (08)

Liner 78 g, brown, bi-siliconized, Paper

Adhesion to Steel O: 2,50 N/25 mm, G: 6,50 N/25 mm

Tensile Strength 159,00 N/25 mm

Temperature Resistance +80°C

Width

Length 50 m, other lengths upon request


6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 23 December 2022





DE-79227 Schallstadt

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of











Technical Product Data Sheet

volzFix 9064V



Applications

- Universally applicable
- Especially good for bonding on rough adhesive surfaces
- Splicing of fabric webs
- Securing panels for printing
- Laying of plastic flooring and carpet with structured backings
- Self-adhesive finishing of decorative material
- Lamination of shoe inserts and heel pads

Benefits

- Can be removed from all clean and gap-solid surfaces without leaving residue
- Tear resistant, flexible cloth backing
- Limited aging and temperature resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15° C to 24° C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15° C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.09.2025











