

Technical Product Data Sheet

volzFix 9064V



volzFix 9064V is a tear-resistant tape coated on both sides, consisting of a cloth carrier and a rubber adhesive. It can be used universally and is suitable for bonding rough surfaces and can be removed without residue.

Nominal Values

Backing Cotton Cloth

Adhesive Type | Natural Rubber

Total Thickness 0,300 mm

Color White (08)

Liner 78 g, brown, bi-siliconized, Paper

Adhesion to Steel O: 2,50 N/25 mm, G: 6,50 N/25 mm

Tensile Strength 159,00 N/25 mm

Temperature Resistance +80°C

Width

Length 50 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 23 December 2022















DE-79227 Schallstadt



Technical Product Data Sheet

volzFix 9064V



Applications

- Universally applicable
- Especially good for bonding on rough adhesive surfaces
- Splicing of fabric webs
- Securing panels for printing
- Laying of plastic flooring and carpet with structured backings
- Self-adhesive finishing of decorative material
- Lamination of shoe inserts and heel pads

Benefits

- Can be removed from all clean and gap-solid surfaces without leaving residue
- Tear resistant, flexible cloth backing
- Limited aging and temperature resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15° C to 24° C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15° C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 02.08.2025













DE-79227 Schallstadt