

volzFix 9065



volzFix 9065 is a double-sided, PET Film with a modified-solvent acrylic. The tape has a very high initial tack, superior adhesion, and outstanding holding power. It is also has excellent resistance against environmental influences, e.g. light, heat and humidity.

Nominal Values

Manufacturer	VOLZ®
Backing	PET Film
Backing Thickness	0,012 mm
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,205 mm
Color	Clear (00)
Liner	Red, MOPP Film
Adhesion to Steel	≥ 20,00 N/25 mm
Shear Strength	≥ 168 h
Rolling Ball Tack	≥ 1 cm
Temperature Resistance	-40°C to +100°C, -40°C to +180°C (short-term)
Length	50 m, 100 m, 500 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1240 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	09 March 2021

volzFix 9065



Applications

- Assembly of ABS parts in the automotive industry
- Self-adhesive finishing of rubber and EPDM
- Strip bonding in the furniture industry
- Sealing of insulation pipe shells
- Display (e.g. mobile phones) and sign bonding
- Equipping lead profiles with self-adhesive
- Convertible automobile top bonding
- Seamless gluing of aluminum sheets
- Roof liner adhesion

Benefits

- Very high initial tack
- Superior adhesion and outstanding holding power
- Excellent resistance against environmental influences, e.g. light, heat and humidity
- Good die-cutting properties

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.07.2024