

volzFix 9070 PV1

volzFix 9070 PV1 is a double-sided adhesive tape with a modified solvent acrylic adhesive. The tape has excellent adhesion and strong holding power. With a PVC backing, the tape has good electrical insulation and good die-cutting properties.

Nominal Values

Backing	PVC Film
Backing Thickness	0,100 mm
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,230 mm (±0,010)
Color	White (08)
Liner	90 g, brown, siliconized Paper
Adhesion to Steel	≥ 41,67 N/25 mm
Shear Strength	≥ 72 h
Temperature Resistance	-20°C to +80°C
Length	50 m, 100 m, 500 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 38 mm, 50 mm, 1240 mm, Other widths by request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	30 June 2026

volzFix 9070 PV1

Applications

- Electrical insulation
- Die-Cuts

Benefits

- Excellent adhesion
- Strong shear strength
- Good die-cutting properties
- Good electrical insulation

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 23°C to 28°C, with a relative humidity of 50%. When using an adhesive tape stored below 23°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 05.07.2026