volzFix 9070 PV1

volzFix 9070 PV1 is a double-sided adhesive tape with a modified solvent acrylic adhesive. The tape has excellent adhesion and strong holding power. With a PVC backing, the tape has good electrical insulation and good die-cutting properties.

Nominal Values

Backing	PVC Film
Backing Thickness	0,100 mm
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,230 mm (±0,010)
Color	White (08)
Liner	90 g, brown, siliconized Paper
Adhesion to Steel	≥ 41,67 N/25 mm
Shear Strength	≥ 72 h
Temperature Resistance	-20°C to +80°C
Length	50 m, 100 m, 500 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 38 mm, 50 mm, 1240 mm, Other widths by request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	30 June 2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix 9070 PV1

Applications

- Electrical insulation
- Die-Cuts

Benefits

- Excellent adhesion
- Strong shear strength
- Good die-cutting properties
- Good electrical insulation

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 23°C to 28°C, with a relative humidity of 50%. When using an adhesive tape stored below 23°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com