volzFix 9072

volzFix 9072 is a very thin, transparent, double-sided tape that is manufactured from polyester-film with a highly-efficient acrylic adhesive. It has excellent adhesion and shear strength.

Nominal Values

Backing	PET Film
Backing Thickness	0,012 mm
Adhesive Type	Acrylic
Total Thickness	0,055 mm
Color	Clear (00)
Liner	White, siliconized Paper
Adhesion to Steel	12,70 N/25 mm
Tensile Strength	49,00 N/25 mm
Elongation at Break	60%
Shear Strength	1 h, 0,80 mm (+40°C x 25mm x 1kg x 1hr)
Temperature Resistance	-40°C to +80°C
Length	50 m, 100 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1040 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	09 March 2021

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

TAPES
Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix 9072

Applications

- Mobile phone and LCD industries

Benefits

- Excellent adhesion and shear strength
- Adhesive allowed residue
- Reliant Bonding Strength
- Free Initial Repositioning in Assembly

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com