

# **Technical Product Data Sheet**

### volzFix 9072L



volzFix 9072L is a double-sided, polyester-film tape with modified-solvent, acrylic adhesive. The tape is widely applied in membrane switch industries and electronic industries.

### **Nominal Values**

**Backing** PET Film

**Backing Thickness** 0,012 mm

**Adhesive Type** | modified, Solvent Acrylic

**Total Thickness** 0,048 mm

**Color** Clear (00)

**Liner** 90 g, white, PE Paper

**Adhesion to Steel** ≥ 12,50 N/25 mm

**Shear Strength** ≥ 168 h

**Rolling Ball Tack** ≥ 10 cm

**Length** 50 m, 5000 m, other lengths upon request


**Width** 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1240


mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 09 March 2021







DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the











## **Technical Product Data Sheet**

### volzFix 9072L



### **Applications**

- Widely applied in membrane switch industries and electronic industries, e.g. mobile phone
- Modular assembly, LCD cushion and reflective film fixation, etc.
- Applications where thin and high transparency are required

#### **Benefits**

- Very thin and transparent, with good adhesion
- Excellent resistant to moisture and plasticizers, which works well in wet environment
- Allows secure bonding to high surface substrates
- Short-term holding of weight is possible

#### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 17.11.2025











