

Technical Product Data Sheet

volzFix 9076P



volzMount 9076P is a double-sided, polyurethane-foam tape coated with acrylic adhesive. Due to its high density, the closed-cell foam offers low compressibility and yet good levelling properties on uneven and rough surfaces.

Nominal Values

Backing PU Foam

Adhesive Type Acrylic

Total Thickness 0,400 mm

> Color Black (04)

Liner white, siliconized Paper

Adhesion to Steel 16,00 N/25 mm

Tensile Strength 220 N/cm2

Elongation at Break 350%

> **Shear Strength** 150 h (+70°C, 0,2 Kg/cm²)

Static Shear 500 h (0,32 Kg/cm²)

Temperature Resistance -40°C to +120°C, +10°C bis +40°C (application temperature)

> Length 60 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1200 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 12 August 2024





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of









Technical Product Data Sheet

volzFix 9076P



Applications

- Mounting of trim, emblems and lettering in the automotive industry
- LED lighting system bonding
- Electronic smart sevice component bonding
- For preventing electrolytic corrosion
- Used especially for high-temperature bonding where a foam backing is required

Benefits

- Strong, thin and flexible foam, keeps its dimensions and shape during punching / clean use
- Predetermined dimension sealant reduces waste
- For indoor and outdoor applications
- High UV-resistance
- Paper release film reduces dimensional change during application
- Good resistance to acids and alkalis
- Minimum compression of 20% for waterproofing

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 27.10.2025



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.









