

volzFix 9080-120



volzFix 9080-120 is a double-sided adhesive tape consisting of a PET carrier coated with a modified solvent acrylic. The tape is Covered on both sides with a 120g white paper liner. It is characterized by a very good adhesion and high temperature resistance, suitable for difficult applications. The tape has a good UV resistance and is compatible with other materials.

Nominal Values

Backing	PET Film
Backing Thickness	0,012 mm
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,080 mm
Color	Clear (00)
Liner	120 g, white, PE Paper
Adhesion to Steel	≥ 15,00 N/25 mm
Loop Tack	≥ 14,00 N/25 mm, FINAT 9
Shear Strength	≥ 168 h, FINAT-8 & ASTM/D3654M-02
Rolling Ball Tack	≥ 4 cm, ASTM3121-94
Temperature Resistance	-20°C to +80°C, -40°C to +120°C (short-term)
Length	50 m, 100 m, 500 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1240 mm, other widths upon request
Storage Life Effective	The material can be stored at room temperature for at least 12 months. 21 February 2022

volzFix 9080-120



Applications

- Application where thinness and high transparency are required
- Membrane switch and electronic industries, e.g. mobile phone modular assembly, LCD cushion and reflective film fixation, etc.

Benefits

- Very thin and transparent, with good adhesion
- Good resistant to moisture, which can work under wet environment
- Allow secure bonding to high energy surface substrates
- Short-term holding of weight is possible

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 28.04.2026