

volzFix 9082 PV2



volzFix 9082 PV2 is a double-sided adhesive tape with different adhesives on each side. One side has a solvent-free acrylic adhesive which is based on aqueous dispersions. The adhesive has a low tack and an peel adhesion that increases moderately with the bonding time. Due to its highly cohesive properties, it can be removed from most substrates without leaving a residue. The other side of the tape has a solvent-free, modified acrylic adhesive, also based on aqueous dispersions. It shows a very good tack combined with a very high adhesive-strength, even on difficult surfaces such as foams and PE or PP films.

Nominal Values

Manufacturer	VOLZ®
Backing	PET Film
Backing Thickness	0,012 mm
Adhesive Type	modified, Dispersion Acrylic, solvent free, Transparent
Total Thickness	0,110 mm, (± 10%)
Color	Clear (00)
Liner	White, siliconized Paper
Adhesion to Steel	≥ 5,00 N/25 mm
Temperature Resistance	-40°C to +90°C
Length	50 m, Other lengths and spools upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	21 November 2022

volzFix 9082 PV2



Applications

- Bonding with resumption function
- Industrial process aids
- Object renovations in event technology
- Exhibition construction and carpet adhesion Object renovations

Benefits

- Open side has permanent adhesion
- Closed side is removable

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 23.11.2024