volzFix 9086-04



volzFix 9086-04 is a double-sided, adhesive tape consisting of a Non-Woven carrier and a black, modified-solvent, acrylic adhesive. It is characterized by very good adhesion and very high temperature resistance and is suitable for difficult applications. The tape has a good UV resistance and is compatible with other materials. It has a very good holding power and can be applied to various surfaces.

Nominal Values

Backing	Non-Woven
Backing Thickness	0,035 mm
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,100 mm
Color	Black (04)
Liner	105 g, white, PE Paper
Adhesion to Steel	≥ 13,00 N/25 mm
Shear Strength	≥ 24 h
Rolling Ball Tack	≥ 9 cm
Temperature Resistance	0°C to +70°C, -20°C to +100°C (short-term)
Length	50 m, 100 m, 1000 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1240 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	23 March 2021

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix 9086-04



Applications

- Installation of ABS parts in the automotive industry
- Installation of ABS parts in the automotive industry, self-finishing PU-foam and EPDM
- Rail bonding in the furniture industry
- For the bonding of signs, panels, scales and door slides in the automotive sector
- For self-adhesive finishing of plastic bags, shipping bags, continuous forms, posters, displays, etc.
- For continuous bonding of paper- and film webs
- For bonding of window panels

Benefits

- Mostly plasticizer resistant
- Very high initial tack and good shear strength

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com